


Wall thickness acc. to AD-2000 code

Capacity: 1.5 litres
A04=40bar
B= BUTYL Rubber Bladder
3/4" Standard Connection
Body & insert material: AISI 316L

Value of "K": $\frac{\text{Maxi. Pressure}}{\text{Filling gas Pressure}} \leq K$ (@Constant Temp.)



TOLERANCES:
External dimintions: $\pm 3\%$
Volume: $\pm 2.5\%$ **Weight:** $\pm 5\%$

7	"O" RING	1	NBR, BUTYL, EPDM & FKM
6	COVER	1	AISI 316L
5	BODY	1	AISI 316L
4.3	RETAINING RING	1	AISI 316
4.2	BOLTS & NUTS	14	DIN 912 & 934 A4-70
4.1	RETAINING RING	2	AISI 316L
4	RETAINING RING	1	DIN17224 (AISI 316)
3	INFLATING N ₂ VALVE	1	AISI 316L (1/4" BSP)
2	INSERT	1	AISI 316L
1.1	"O" RING	1	NBR, BUTYL, EPDM & FKM
1	BLADDER	1	NBR, BUTYL, EPDM & FKM
No	DENOMINATION	QT.	MATERIALS



<i>Rev.</i>	<i>Date</i>	<i>Scale</i>
24	Sep-19	none